Hisense

продуктов фиш

Indoor Model	KA50BS0EG
Outdoor Model	KA50BS0EW
Sound Power Level at Standard Rating Conditions (Indoor / Outdoor)[db(A)]	60 / 63
Refrigerant Type	R32
GWP	675
Charge amount	1150
CO2 equivalent (tonnes)	0,776
SEER	7,8
Energy efficiency Class in cooling	A++
Annual Electricity Consumption in Cooling [kWh/year][1]	224
Design Load in cooling Mode (Pdesign)[KW]	5,0
SCOP (average heating season)	4,6
Energy efficiency class in heating (average season)	A++
Annual Electricity Consumption in heating (average season)[kWh/year][2]	1187
Warmer heating season [kW]	5,0
Colder heating season [kW]	<u></u>
Design load in heating mode (Pdesign)[KW]	5,0
Declared capacity at reference design condition (heating average season)[KW]	3,90
Back up heating capacity at reference design condition (heating average season)[KW]	

Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere. This appliance contains a refrigerant fluid with a GWP equal to 675. This means that if 1kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be 675 times higher than 1kg of CO2, over a period of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself and always ask a professional.

Contains flourinated greenhouse gases

Importer: Partizanska 12, 3320 Velenje, Slovenija info@gorenje.si / +386 3 899 1000

Manufacturer: Partizanska 12, 3320 Velenje, Slovenija info@gorenje.si / +386 3 899 1000

[1][2] Energy consumtion "XYZ" [kWh] per year, based on standard test result. Actual energy consumption will depend on how the appliance is used and where it is located.

Note: Please check the model information above according to the model name on the nameplate